



Product Data Sheet

Performance Machine Stretch Film (Bio-degradable)



Effective 08/2018

Item ID Number: PMF2063A- Bio

Product description: -

This film is made with 1% d2w bio-degradable additive from Symphony Environment. It converts film at the end of their useful life in the presence of oxygen into materials which degrade, and then biodegrade in the open environment in the same way as nature’s waste and leaving nothing behind – no toxic residues or fragments of plastic.

Nominal Values: (Tol. +/-15%)

Film Properties	ASTM Test Method	80 Gauge
Tensile @ Break MD (psi)	D-882	6,600
Tensile @ Break TD (psi)	D-882	5750
Tensile @ Yield MD (psi)	D-882	1,550
Tensile @ Yield TD (psi)	D-882	1,370
Elongation MD (%)	D-882	610
Elongation TD (%)	D-882	810
Elmendorf Tear MD (g/mil)	D-1922	350
Elmendorf Tear TD (g/mil)	D-1922	625

Wrap Tite, Inc.

6200 Cochran Rd.
Solon, Ohio 44139

Toll Free: 888-WRAP TITE (972-7848)

Fax: 440-349-5432

www.wraptite.com – info@wraptite.com



NOTE: MD = Machine Direction

TD = Transverse Direction